

**Thermocouple Wire**

OHKUYO

**Extension Wire**

Part No.	Description	Max. Temp.	Sample
WCA-H-7/0.3x2	Fiberglass / Type K (Blue Colour) 2*7*0.3	0 - 400°C	
GG-K-24	Omega Fiberglass / Type K (Brown Colour) 2*1*0.5	0 - 480°C	
WCA-S-4/0.65x2	Silicon Rubber / Type K (Blue Colour) 2*4*0.65	0 - 200°C	
WCA-G-4/0.6x2	PVC / Type K (Blue Colour) 2*4*0.65	0 - 105°C	
TC-CA-H(SOS)-4/0.3x2	SUS 304 Screen Cable / Type K (Teflon) 2*4*0.32	0 - 400°C	
TC-PT-H(SOS)-1/0.6x3	SUS 304 Screen Cable / PT100 (Teflon) 3*24AWG	0 - 200°C	
RTD-TEF-24AWG	Teflon / PT100 (White Colour) 3*24AWG	0 - 200°C	

**High-Temp Heater Wire**

Fiberglass Outer Insulation  
Silicone Rubber Inner Insulation  
Good Resistance for Thermal Shock  
Excellent Ageing Resistance



Part No.	mm <sup>2</sup>	Packing
20/0.18	0.5mm <sup>2</sup>	100M/Coil
24/0.20	0.75mm <sup>2</sup>	100M/Coil
32/0.20	1mm <sup>2</sup>	100M/Coil
30/0.25	1.5mm <sup>2</sup>	100M/Coil
40/0.25	2mm <sup>2</sup>	100M/Coil
49/0.25	2.5mm <sup>2</sup>	100M/Coil
42/0.30	3mm <sup>2</sup>	100M/Coil
49/0.30	3.5mm <sup>2</sup>	100M/Coil
56/0.30	4mm <sup>2</sup>	100M/Coil
70/.030	5mm <sup>2</sup>	100M/Coil
77/0.30	5.5mm <sup>2</sup>	100M/Coil
84/0.30	6mm <sup>2</sup>	100M/Coil
	8mm <sup>2</sup>	100M/Coil
84/0.39	10mm <sup>2</sup>	100M/Coil
210/0.39	25mm <sup>2</sup>	100M/Coil

**Sleeving**

Fiberglass Outer Insulation



ID (mm)	Description	Packing
2	Fiberglass Sleeving	100M/Coil
3	Fiberglass Sleeving	100M/Coil
4	Fiberglass Sleeving	100M/Coil
6	Fiberglass Sleeving	100M/Coil
8	Fiberglass Sleeving	100M/Coil
10	Fiberglass Sleeving	100M/Coil
12	Fiberglass Sleeving	100M/Coil
14	Fiberglass Sleeving	100M/Coil
20	Fiberglass Sleeving	100M/Coil
22	Fiberglass Sleeving	100M/Coil

**Thermocouple Connector**



Part No.	Description
K-11	Type-K Miniature Male Connector
K-12	Type-K Miniature Female Connector
K-13	Type-K Mini Wall Female Connector
T-11	Type-T Miniature Male Connector
T-12	Type-T Miniature Female Connector

OY-01